

SCM25Ai Pro *Mk2*

Compact Active 3-way Studio Monitor

Overview

Compact high performance 3-way studio monitor suitable for installed applications.

1-channel, 2-channel & 3-channel 19" rack mount remote amp options.

Reinforced wall/ceiling bracket mount compatible cabinet.

Suitable for use in stereo, surround and immersive audio applications.

Free-standing version with on-board amp also available – SCM25A Pro Mk2.

Acoustic specifications

Drive Units: Bass: 1 x SB50-164SC 8Ω

Mid: 1 x SM75-150 16Ω

HF: 1 x SH25-76S 6Ω Compact.

Low Frequency Cut-off: 47Hz (-6dB, anechoic).

High Frequency Cut-off: 25kHz (-6dB).

MaxSPL: 109dB continuous, 115dB peak (per pair, IEC Weighted Pink Noise, 1m, anechoic).

Sensitivity: -15dBu ref 85dBC (Bass Boost 0dB, Input Sensitivity 1V, Pink noise).

Speaker Level Input: 1 x Rear Panel Mounted Neutrik NL8.

Power/Clip LED Input: 1 x Rear Panel Mounted 5-Pin Female XLR.

Electronic Specifications

See data for chosen remote amplifier; selected from: R1-234 Pro (1-channel, 6U)

R2-234 Pro (2-channel, 5U)

R3-234 Pro (3-channel, 5U)

Physical specifications

See following page.

SCM25Ai Pro Mk2

Compact Active 3-way Studio Monitor

Net Weight: 19.3kg/42.5lbs.

Dimensions...

SCM25Ai PRO MK2

