

# SCM20PSL

## 2-Way Passive Stand-Mount Loudspeaker

### Overview

- Compact sealed cabinet
- Proprietary ATC 1"/25mm 'S-Spec' H.F. driver
- Proprietary ATC 6"/150mm 'SL' bass driver
- On-board ATC active 250W 'Amp Pack'
- Class A/B MOSFET amplifiers, 200W mid-bass & 50W high-frequency
- 2nd order Linkwitz-Riley active crossovers
- User adjustable input sensitivity & bass shelf controls

### Acoustic specifications

- Mid/Bass driver: 1 x 150mm/6", SB75-150SL 8Ω
- High Frequency Driver: 1 x 25mm/1", SH25-76S 6Ω
- Low Frequency Cut-off: 55Hz (-6dB, anechoic)
- High Frequency Cut-off: 25kHz (-6dB)
- Matched Response: +/-0.5dB
- Crossover Point: 2.2kHz
- MaxSPL: 108dB continuous, 114dB peak (per pair; IEC Weighted Pink Noise, 1m, anechoic).
- System Sensitivity: 85dB (1W @1m)

### Electronic specifications

- Recommended Power Amplifier: 75W-300W
- Impedance: 8Ω nominal/5.5Ω minimum

### Physical specifications

See following page



ATC reserve the right to change specifications without prior notice  
 Acoustic Transducer Co. Is a trading name and ATC is the registered Trade Mark of Loudspeaker Technology Ltd.

# SCM20PSL

## 2-Way Passive Stand-Mount Loudspeaker

Net Weight: 16.9kg/37.3lbs

Dimensions...

SCM20PSL

